CARING FOR YOUR NEW BOARD

Your board has been conditioned before shipping, however routine care for your new board is essential, here are some basic guidelines. After each use scrub your board with a nylon bristle dish brush using a mild dish soap and water, then rinse and thoroughly dry with a clean cotton towel.

DO NOT RUN THE BOARD THROUGH THE DISHWASHER OR LET IT SIT IN WATER.

To help keep your board sealed use a butcher block conditioner. You can purchase this at your local home center or you can easily make your own.

CUTTING BOARD WAX/OIL RECIPE;

1 cup of mineral oil OR refined coconut oil 2 ounces of beeswax

Pour the oil into a pan and add the beeswax. Melt over low heat and keep stirring until the beeswax has completely dissolved. Once the mixture has fully blended together pour into a glass jar and let it cool. Once cooled this mixture will gel. Work the wax on your board in a circular motion with a cotton cloth then wipe off the excess wax with a separate cotton cloth. Apply wax to your board once every 1-2 weeks to keep it conditioned.

Please feel free to contact me with any questions at: ron@rondepewwoodworking.com 615-305-7755

www.rondepewwoodworking.com

CARING FOR YOUR NEW BOARD

Your board has been conditioned before shipping, however routine care for your new board is essential, here are some basic guidelines. After each use scrub your board with a nylon bristle dish brush using a mild dish soap and water, then rinse and thoroughly dry with a clean cotton towel.

DO NOT RUN THE BOARD THROUGH THE DISHWASHER OR LET IT SIT IN WATER.

To help keep your board sealed use a butcher block conditioner. You can purchase this at your local home center or you can easily make your own.

CUTTING BOARD WAX/OIL RECIPE;

1 cup of mineral oil OR refined coconut oil 2 ounces of beeswax

Pour the oil into a pan and add the beeswax. Melt over low heat and keep stirring until the beeswax has completely dissolved. Once the mixture has fully blended together pour into a glass jar and let it cool. Once cooled this mixture will gel. Work the wax on your board in a circular motion with a cotton cloth then wipe off the excess wax with a separate cotton cloth. Apply wax to your board once every 1-2 weeks to keep it conditioned.

Please feel free to contact me with any questions at: ron@rondepewwoodworking.com 615-305-7755

www.rondepewwoodworking.com